

according to UK REACH Regulation

DEKACLEAN ULTRA TOWEL

Revision date: 20.01.2025 Product code: 1227 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DEKACLEAN ULTRA TOWEL

UFI: 6HY2-Y1JW-7002-XF7P

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

detergent

Uses advised against

No further relevant information available.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: DINOL GmbH

Street: Pyrmonter Strasse 76
Place: D-32676 Luegde

Telephone: + 49 (0) 5281 982980 Telefax: + 49 (0) 5281 9829860

E-mail: msds@dinol.com

Contact person: Labor

Responsible Department: msds@dinol.com

Supplier

Company name:

Street:

Marston Business Park, Rudgate
Place:

GB Tockwith, York YO26 7QF

E-mail:

enquiries@leading-solvents.co.uk

www.leading-solvents.co.uk

1.4. Emergency telephone Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

isopropanol (isopropyl alcohol) **Signal word:**Danger

Pictograms:





Hazard statements

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.



according to UK REACH Regulation

DEKACLEAN ULTRA TOWEL

Revision date: 20.01.2025 Product code: 1227 Page 2 of 11

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P243 Take action to prevent static discharges.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool. Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:





2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name	Chemical name		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
67-63-0	isopropanol (isopropyl alcohol)			70 - < 75 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. L	cific Conc. Limits, M-factors and ATE	
67-63-0	200-661-7	isopropanol (isopropyl alcohol)	
	inhalation: LC50 = 30 mg/l (vapours); dermal: LD50 = 13400 mg/kg; oral: LD50 = 4570 mg/kg		

Further Information

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.



according to UK REACH Regulation

DEKACLEAN ULTRA TOWEL

Revision date: 20.01.2025 Product code: 1227 Page 3 of 11

After contact with skin

Change contaminated clothing.

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Irritating to eyes. May cause drowsiness or dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Extinguishing powder. Water spray jet alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Dilute with plenty of water.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.



according to UK REACH Regulation

DEKACLEAN ULTRA TOWEL

Revision date: 20.01.2025 Product code: 1227 Page 4 of 11

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Store in a cool dry place.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage

No information available.

Further information on storage conditions

No information available.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
67-63-0	67-63-0 isopropanol (isopropyl alcohol)					
Consumer DNEL, long-term		inhalation	systemic	89 mg/m³		
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day		
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day		
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day		
Worker DNEL, long-term		inhalation	systemic	500 mg/m³		



according to UK REACH Regulation

DEKACLEAN ULTRA TOWEL

Product code: 1227 Revision date: 20.01.2025 Page 5 of 11

PNEC values

CAS No	Cubatana			
CAS NO	Substance			
Environmen	tal compartment	Value		
67-63-0	isopropanol (isopropyl alcohol)			
Freshwater		140,9 mg/l		
Marine water		140,9 mg/l		
Freshwater sediment		552 mg/kg		
Marine sediment		552 mg/kg		
Secondary poisoning		160 mg/kg		
Micro-organisms in sewage treatment plants (STP)		2251 mg/l		
Soil		28 mg/kg		

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (DIN EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.

NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141). Filter material/medium:

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: colourless Odour: characteristic Odour threshold: not determined

Melting point/freezing point: not determined Boiling point or initial boiling point and > 80 °C

boiling range:

Flammability: not determined Lower explosion limits: 2,21 vol. % Upper explosion limits: 12.0 vol. % Flash point: 13 °C not determined Auto-ignition temperature:



according to UK REACH Regulation

DEKACLEAN ULTRA TOWEL

Revision date: 20.01.2025 Product code: 1227 Page 6 of 11

Decomposition temperature: not applicable pH-Value (at 20 °C): 8,3 Viscosity / kinematic: not applicable Water solubility: completely miscible

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: 43 hPa

(at 20 °C)

Density (at 20 °C): 0,8 g/cm³
Relative vapour density: not determined
Particle characteristics: not applicable

9.2. Other information

Information with regard to physical hazard classes

Explosive properties not determined Oxidizing properties not determined

Other safety characteristics

Solvent content: 65, %
Solid content: 20 %
Softening point: not determined
Viscosity / dynamic: not applicable

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

No known hazardous decomposition products.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

10.5. Incompatible materials

Strong acid, Oxidizing agent

10.6. Hazardous decomposition products

none

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



according to UK REACH Regulation

DEKACLEAN ULTRA TOWEL

Revision date: 20.01.2025 Product code: 1227 Page 7 of 11

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
67-63-0	isopropanol (isopropyl alcohol)					
	oral	LD50 mg/kg	4570	Rat		
	dermal	LD50 mg/kg	13400	Rabbit		
	inhalation (4 h) vapour	LC50	30 mg/l	Rat		

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (isopropanol (isopropyl alcohol))

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No information available.

Specific effects in experiment on an animal

No information available.

Additional information on tests

No information available.

Practical experience

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

No further relevant information available.

12.3. Bioaccumulative potential

No further relevant information available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	isopropanol (isopropyl alcohol)	0,05



according to UK REACH Regulation

DEKACLEAN ULTRA TOWEL

Revision date: 20.01.2025 Product code: 1227 Page 8 of 11

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No further relevant information available.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

Do not mix with other wastes.

List of Wastes Code - residues/unused products

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation,

supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and

mother liquors; hazardous waste

List of Wastes Code - contaminated packaging

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation,

supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and

mother liquors; hazardous waste

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 601
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):



according to UK REACH Regulation

DEKACLEAN ULTRA TOWEL

Revision date: 20.01.2025 Product code: 1227 Page 9 of 11

14.4. Packing group:
Hazard label:
3



Classification code: F1
Special Provisions: 601
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions:

Limited quantity:

Excepted quantity:

E2

EmS:

F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1219

14.2. UN proper shipping name: ISOPROPYL ALCOHOL

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A180

1 L

Y341

Excepted quantity:

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

Hazchem code: •2YE

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information



according to UK REACH Regulation

DEKACLEAN ULTRA TOWEL

Revision date: 20.01.2025 Product code: 1227 Page 10 of 11

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in 29,8 % paints and varnishes: 287,272 g/l

Information according to Directive

P5c FLAMMABLE LIQUIDS

2012/18/EU (SEVESO III):

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the

Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

For this substance a chemical safety assessment has been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 16.

Abbreviations and acronyms

Flam. Liq: Flammable liquids

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our

Print date: 27.02.2025



Safety Data Sheet

according to UK REACH Regulation

DEKACLEAN ULTRA TOWEL

Revision date: 20.01.2025 Product code: 1227 Page 11 of 11

present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)