

# Safety Data Sheet

according to UK REACH Regulation

## DEKAPHON PRO WAX

Revision date: 18.12.2024

Product code: 0180

Page 1 of 14

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

DEKAPHON PRO WAX

UFI: XYV0-HKCX-700R-4K8R

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Anti-corrosive coating

##### Uses advised against

No further relevant information available.

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Company name: DINOL GmbH  
Street: Pyrmonter Strasse 76  
Place: D-32676 Luegde  
Telephone: + 49 (0) 5281 982980  
E-mail: msds@dinol.com  
Contact person: Labor  
Responsible Department: msds@dinol.com

Telefax: + 49 (0) 5281 9829860

##### Supplier

Company name: Leading Solvent Supplies Limited  
Street: Marston Business Park, Rudgate  
Place: GB Tockwith, York YO26 7QF  
E-mail: enquiries@leading-solvents.co.uk  
Internet: www.leading-solvents.co.uk

#### 1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GB CLP Regulation

Aerosol 1; H222-H229  
Asp. Tox. 1; H304  
STOT SE 3; H336  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

##### GB CLP Regulation

##### Hazard components for labelling

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics  
pentane

Signal word: Danger

Pictograms:



## Safety Data Sheet

according to UK REACH Regulation

### DEKAPHON PRO WAX

Revision date: 18.12.2024

Product code: 0180

Page 2 of 14

#### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### Special labelling of certain mixtures

EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains calcium sulfonate. May produce an allergic reaction.

#### Additional advice on labelling

The classification of the aerosol was carried out according to EC 1272/2008, Annex 1, point 1.1.3.7.

#### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



#### Precautionary statements

P210-P211-P251-P410+P412

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

## Safety Data Sheet

according to UK REACH Regulation

### DEKAPHON PRO WAX

Revision date: 18.12.2024

Product code: 0180

Page 3 of 14

#### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			45 - < 50 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304			
106-97-8	butane			10 - < 15 %
	203-448-7	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Compressed gas; H220 H280			
74-98-6	propane			10 - < 15 %
	200-827-9		01-2119486944-21	
	Flam. Gas 1A, Compressed gas; H220 H280			
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			5 - < 10 %
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412			
109-66-0	pentane			5 - < 10 %
	203-692-4	601-006-00-1	01-2119459286-30	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066			
61789-86-4	calcium sulfonate			1 - < 5 %
	263-093-9		01-2119488992-18	
	Skin Sens. 1B; H317			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	45 - < 50 %
		dermal: LD50 = >3000 mg/kg; oral: LD50 = > 5000 mg/kg	
	927-241-2	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	5 - < 10 %
		inhalation: LC50 = 4951 mg/l (vapours); dermal: LD50 = 5000 mg/kg; oral: LD50 = 4951 mg/kg	
109-66-0	203-692-4	pentane	5 - < 10 %
		inhalation: LC50 = > 25,3 mg/l (vapours); oral: LD50 = >5000 mg/kg	
61789-86-4	263-093-9	calcium sulfonate	1 - < 5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 5000 mg/kg Skin Sens. 1B; H317: >= 10 - 100	

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

##### After inhalation

Provide fresh air.

##### After contact with skin

In case of skin irritation, consult a physician.

**Safety Data Sheet**

according to UK REACH Regulation

**DEKAPHON PRO WAX**

Revision date: 18.12.2024

Product code: 0180

Page 4 of 14

**After contact with eyes**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

**After ingestion**

Call a physician immediately. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>) Extinguishing powder Water spray jet alcohol resistant foam.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

No further relevant information available.

**5.3. Advice for firefighters**

Use suitable breathing apparatus.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

**For emergency responders**

For further specification, refer to section 8 of the SDS.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

**6.3. Methods and material for containment and cleaning up****For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

**For cleaning up**

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

**Other information**

No information available.

**6.4. Reference to other sections**

Safe handling: see section 7

## Safety Data Sheet

according to UK REACH Regulation

### DEKAPHON PRO WAX

Revision date: 18.12.2024

Product code: 0180

Page 5 of 14

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Provide adequate ventilation as well as local exhaust at critical locations.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

#### Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Remove contaminated, saturated clothing immediately.

Do not breathe gas/vapour/aerosol.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Do not keep the container sealed. Keep container dry.

Keep away from heat. Protect from direct sunlight.

#### Hints on joint storage

Not required.

#### Further information on storage conditions

Keep container tightly closed.

### 7.3. Specific end use(s)

No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
109-66-0	Pentane	600	1800		TWA (8 h)	WEL

## Safety Data Sheet

according to UK REACH Regulation

### DEKAPHON PRO WAX

Revision date: 18.12.2024

Product code: 0180

Page 6 of 14

#### DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			
Worker DNEL, long-term		inhalation	systemic	871 mg/m³
Worker DNEL, long-term		dermal	systemic	208 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	185 mg/m³
Consumer DNEL, long-term		dermal	systemic	125 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	125 mg/kg bw/day
109-66-0	pentane			
Worker DNEL, long-term		inhalation	systemic	3000 mg/m³
Worker DNEL, long-term		dermal	systemic	432 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	643 mg/m³
Consumer DNEL, long-term		dermal	systemic	214 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	214 mg/kg bw/day
61789-86-4	calcium sulfonate			
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day
Worker DNEL, long-term		dermal	local	1,03 mg/cm²
Consumer DNEL, long-term		inhalation	systemic	2,9 mg/m³
Consumer DNEL, long-term		dermal	systemic	1,667 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,513 mg/cm²
Consumer DNEL, long-term		oral	systemic	0,8333 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	11,75 mg/m³

#### PNEC values

CAS No	Substance	
Environmental compartment	Value	
109-66-0	pentane	
Freshwater	0,230 mg/l	
Marine water	0,230 mg/l	
Freshwater sediment	1,2 mg/kg	
Marine sediment	1,2 mg/kg	
Micro-organisms in sewage treatment plants (STP)	3,600 mg/l	
61789-86-4	calcium sulfonate	
Freshwater	1 mg/l	
Marine water	1 mg/l	
Freshwater sediment	226000000 mg/kg	
Marine sediment	226000000 mg/kg	
Secondary poisoning	16667 mg/kg	
Micro-organisms in sewage treatment plants (STP)	1000 mg/l	
Soil	271000000 mg/kg	

## Safety Data Sheet

according to UK REACH Regulation

### DEKAPHON PRO WAX

Revision date: 18.12.2024

Product code: 0180

Page 7 of 14

#### 8.2. Exposure controls



##### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Eye glasses with side protection (EN 166)

##### Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time::

PVA (Polyvinyl alcohol), Breakthrough time::

NBR (Nitrile rubber), Breakthrough time::

Butyl caoutchouc (butyl rubber), Breakthrough time::

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

##### Skin protection

Wear anti-static footwear and clothing

##### Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141), Filter material/medium: AX

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	whitish
Odour:	characteristic
Odour threshold:	not determined

	Test method
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	-44,5 °C
Flammability:	not applicable
Lower explosion limits:	not applicable
Upper explosion limits:	0,6 vol. %
Flash point:	10,9 vol. %
Auto-ignition temperature:	-97 °C
Decomposition temperature:	460 °C
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	practically insoluble

# Safety Data Sheet

according to UK REACH Regulation

## DEKAPHON PRO WAX

Revision date: 18.12.2024

Product code: 0180

Page 8 of 14

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

not determined

Vapour pressure:

8300 hPa

(at 20 °C)

Vapour pressure:

13 hPa

(at 50 °C)

Density (at 20 °C):

0,72 g/cm<sup>3</sup> DIN 51757

Relative vapour density:

not determined

### 9.2. Other information

#### Information with regard to physical hazard classes

Explosive properties

not determined

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

not determined

#### Other safety characteristics

Evaporation rate:

not determined

Solvent content:

77,5 %

Solid content:

24,6 %

Viscosity / dynamic:

not determined

#### Further Information

VOC (EU) 75,42 %

VOC (EU) 540,0 g/l

VOCV 77,46 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No further relevant information available.

### 10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

### 10.4. Conditions to avoid

No further relevant information available.

### 10.5. Incompatible materials

No further relevant information available.

### 10.6. Hazardous decomposition products

Carbon monoxide

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) 4,545 mg/l



# Safety Data Sheet

according to UK REACH Regulation

## DEKAPHON PRO WAX

Revision date: 18.12.2024

Product code: 0180

Page 9 of 14

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 >3000 mg/kg	Rat		
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 4951 mg/kg	Rat		
	dermal	LD50 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 4951 mg/l	Rat		
109-66-0	pentane				
	oral	LD50 >5000 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 > 25,3 mg/l	Rat		
61789-86-4	calcium sulfonate				
	oral	LD50 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		

### Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

### Sensitising effects

Based on available data, the classification criteria are not met.

Contains calcium sulfonate. May produce an allergic reaction.

### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

### STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration hazard

May be fatal if swallowed and enters airways.

## 11.2. Information on other hazards

### Endocrine disrupting properties

Endocrine disrupting potential No information available.

### Further information

There are no data available on the preparation/mixture itself.

## SECTION 12: Ecological information

### 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

## Safety Data Sheet

according to UK REACH Regulation

### DEKAPHON PRO WAX

Revision date: 18.12.2024

Product code: 0180

Page 10 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
109-66-0	pentane					
	Acute fish toxicity	LC50 mg/l	4,26	96 h	fish	
	Acute crustacea toxicity	EC50	9,7 mg/l	48 h	Daphnia magna	IUCLID

#### 12.2. Persistence and degradability

No further relevant information available.

#### 12.3. Bioaccumulative potential

No further relevant information available.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36

#### 12.4. Mobility in soil

No further relevant information available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No further relevant information available.

#### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

##### List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

##### List of Wastes Code - contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

##### Contaminated packaging

Dispose of waste according to applicable legislation.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

##### 14.1. UN number or ID number:

UN 1950

# Safety Data Sheet

according to UK REACH Regulation

## DEKAPHON PRO WAX

Revision date: 18.12.2024

Product code: 0180

Page 11 of 14

**14.2. UN proper shipping name:** AEROSOLS

**14.3. Transport hazard class(es):** 2

**14.4. Packing group:** -

Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L

Excepted quantity: E0

Transport category: 2

Tunnel restriction code: D

**Other applicable information (land transport)**

E0

### Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN 1950

**14.2. UN proper shipping name:** AEROSOLS

**14.3. Transport hazard class(es):** 2

**14.4. Packing group:** -

Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L

Excepted quantity: E0

### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1950

**14.2. UN proper shipping name:** AEROSOLS

**14.3. Transport hazard class(es):** 2.1

**14.4. Packing group:** -

Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 381, 959

Limited quantity: 1000 mL

Excepted quantity: E0

EmS: F-D, S-U

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 1950

**14.2. UN proper shipping name:** AEROSOLS, FLAMMABLE

**14.3. Transport hazard class(es):** 2.1

**14.4. Packing group:** -

Hazard label: 2.1



Special Provisions: A145 A167 A802

## Safety Data Sheet

according to UK REACH Regulation

### DEKAPHON PRO WAX

Revision date: 18.12.2024

Product code: 0180

Page 12 of 14

Limited quantity Passenger:	30 kg G	
Passenger LQ:	Y203	
Excepted quantity:	E0	
IATA-packing instructions - Passenger:		203
IATA-max. quantity - Passenger:		75 kg
IATA-packing instructions - Cargo:		203
IATA-max. quantity - Cargo:		150 kg

#### Other applicable information (air transport)

E0

Passenger-LQ: Y203

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

Warning: Gases under pressure

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

#### Other applicable information

Stowage Code:

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code:

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

Directive 2004/42/EC on VOC in	75,42 %
paints and varnishes:	540,0 g/l

##### Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

##### National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
--------------------------	---

Water hazard class (D):	2 - obviously hazardous to water
-------------------------	----------------------------------

##### Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

# Safety Data Sheet

according to UK REACH Regulation

## DEKAPHON PRO WAX

Revision date: 18.12.2024

Product code: 0180

Page 13 of 14

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 2,16.

#### Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols

Compressed gas

Flam. Liq: Flammable liquids

Asp. Tox: Aspiration hazard

Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

#### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains calcium sulfonate. May produce an allergic reaction.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

**Safety Data Sheet**

according to UK REACH Regulation

**DEKAPHON PRO WAX**

Revision date: 18.12.2024

Product code: 0180

Page 14 of 14

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*