

according to UK REACH Regulation

DEKAPREN 1513/4

Revision date: 09.04.2025 Product code: 1078 Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DEKAPREN 1513/4

UFI: SHRT-3K4T-500A-0F7S

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Sizing agent

Uses advised against

No further relevant information available.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: DINOL GmbH

Street: Pyrmonter Strasse 76
Place: D-32676 Luegde

Telephone: + 49 (0) 5281 982980 Telefax: + 49 (0) 5281 9829860

E-mail: msds@dinol.com

Contact person: Labor

Responsible Department: msds@dinol.com

Supplier

Company name:

Street:

Marston Business Park, Rudgate
Place:

GB Tockwith, York YO26 7QF

E-mail:

enquiries@leading-solvents.co.uk

www.leading-solvents.co.uk

1.4. Emergency telephone Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225 Carc. 2; H351 Eye Irrit. 2; H319 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

acetone; propan-2-one; propanone

ethyl acetate methyl acetate

4-methylpentan-2-one, isobutyl methyl ketone

Signal word: Danger

Print date: 09.04.2025



Safety Data Sheet

according to UK REACH Regulation

DEKAPREN 1513/4

Revision date: 09.04.2025 Product code: 1078 Page 2 of 17

Pictograms:







Hazard statements

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H351 Suspected of causing cancer.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P243 Take action to prevent static discharges.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:







Hazard statements

H351

Precautionary statements

P280-P405

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures



according to UK REACH Regulation

DEKAPREN 1513/4

Revision date: 09.04.2025 Product code: 1078 Page 3 of 17

Relevant ingredients

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation)	,			
67-64-1	acetone; propan-2-one; propanone			35 - < 40 %	
	200-662-2	606-001-00-8	01-2119471330-49		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE				
141-78-6	ethyl acetate			15 - < 20 %	
	205-500-4	607-022-00-5	01-2119475103-46		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE				
79-20-9	methyl acetate			5 - < 10 %	
	201-185-2		01-2119459211-47		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE	3; H225 H319 H336 EUH066	•		
108-10-1	4-methylpentan-2-one, isobutyl me	thyl ketone		1 - < 5 %	
	203-550-1	606-004-00-4	01-2119473980-30		
	Flam. Liq. 2, Carc. 2, Acute Tox. 4, EUH066	Eye Irrit. 2, STOT SE 3; H225 H35	1 H332 H319 H336		
123-86-4	n-butyl acetate			1 - < 5 %	
	204-658-1	607-025-00-1	01-2119485493-29		
	Flam. Liq. 3, STOT SE 3; H226 H3	36 EUH066			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
67-64-1	200-662-2	acetone; propan-2-one; propanone	35 - < 40 %
	inhalation: LC5 mg/kg	0 = 76 mg/l (vapours); dermal: LD50 = 7426-15800 mg/kg; oral: LD50 = 5800	
141-78-6	205-500-4	ethyl acetate	15 - < 20 %
	inhalation: LC5	60 = 50 mg/l (vapours); dermal: LD50 = >20000 mg/kg; oral: LD50 = 5620 mg/kg	
79-20-9	201-185-2	methyl acetate	5 - < 10 %
	inhalation: LC5	i0 = >49 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	
108-10-1	203-550-1	4-methylpentan-2-one, isobutyl methyl ketone	1 - < 5 %
	inhalation: ATE	11 mg/l (vapours); oral: LD50 = 2080 mg/kg	
123-86-4	204-658-1	n-butyl acetate	1 - < 5 %
		60 = > 21 mg/l (vapours); inhalation: LC50 = >21 mg/l (dusts or mists); dermal: 2 mg/kg; oral: LD50 = 10760 mg/kg	

Further Information

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.



according to UK REACH Regulation

DEKAPREN 1513/4

Revision date: 09.04.2025 Product code: 1078 Page 4 of 17

After contact with skin

Change contaminated clothing.

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Do NOT induce vomiting.

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Extinguishing powder,

Unsuitable extinguishing media

High power water jet. water

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Use appropriate respiratory protection.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.



according to UK REACH Regulation

DEKAPREN 1513/4

Revision date: 09.04.2025 Product code: 1078 Page 5 of 17

Clear contaminated areas thoroughly.

Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in a cool dry place.

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed.

Keep in a cool, well-ventilated place.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to UK REACH Regulation

DEKAPREN 1513/4

Revision date: 09.04.2025 Product code: 1078 Page 6 of 17

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
108-10-1	4-Methylpentan-2-one	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
141-78-6	Ethyl acetate	200	734		TWA (8 h)	WEL
		400	1468		STEL (15 min)	WEL
79-20-9	Methyl acetate	200	616		TWA (8 h)	WEL
		250	770		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
108-10-1	4-methylpentan-2-one	4-methylpentan-2-one	20 µmol/L	urine	Post shift



according to UK REACH Regulation

DEKAPREN 1513/4

Revision date: 09.04.2025 Product code: 1078 Page 7 of 17

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
67-64-1	acetone; propan-2-one; propanone			
Worker DNEI	L, long-term	inhalation	systemic	1210 mg/m³
Worker DNEI	L, acute	inhalation	local	2420 mg/m³
Worker DNEI	L, long-term	dermal	systemic	186 mg/kg bw/da
Consumer DI	NEL, long-term	inhalation	systemic	200 mg/m ³
Consumer DI	NEL, long-term	dermal	systemic	62 mg/kg bw/day
Consumer DI	NEL, long-term	oral	systemic	62 mg/kg bw/day
1				
141-78-6	ethyl acetate			
Worker DNEI	L, long-term	inhalation	systemic	734 mg/m³
Worker DNEI	L, acute	inhalation	systemic	1468 mg/m³
Worker DNEI	L, long-term	inhalation	local	734 mg/m³
Worker DNEI	L, acute	inhalation	local	1468 mg/m³
Worker DNEI	L, long-term	dermal	systemic	63 mg/kg bw/day
Consumer DI	NEL, long-term	inhalation	systemic	367 mg/m³
Consumer DI	NEL, acute	inhalation	systemic	734 mg/m³
Consumer DI	NEL, long-term	dermal	systemic	37 mg/kg bw/day
Consumer DI	NEL, long-term	oral	systemic	4,5 mg/kg bw/da
79-20-9	methyl acetate			
Worker DNEI	L, long-term	dermal	systemic	43 mg/kg bw/day
Worker DNEI	L, long-term	inhalation	local	620 mg/m³
Consumer DI	NEL, long-term	dermal	systemic	21,5 mg/kg bw/day
Consumer DI	NEL, long-term	inhalation	systemic	64 mg/m³
Worker DNE	L, long-term	inhalation	systemic	300 mg/m ³
Worker DNE	L, acute	inhalation	systemic	3777 mg/m³
Consumer DI	NEL, long-term	oral	systemic	203 mg/kg bw/da
Consumer DI	NEL, acute	dermal	systemic	203 mg/kg bw/da
Consumer DI	NEL, acute	oral	systemic	203 mg/kg bw/da
108-10-1	4-methylpentan-2-one, isobutyl methyl ketor	ne		
Worker DNE	L, long-term	inhalation	systemic	83 mg/m³
Worker DNE	L, acute	inhalation	local	208 mg/m³
Worker DNEI	L, long-term	dermal	systemic	11,8 mg/kg bw/day
Worker DNE	L, acute	inhalation	systemic	208 mg/m³
Worker DNEI	L, long-term	inhalation	local	83 mg/m³
Consumer DI	NEL, long-term	inhalation	systemic	14,7 mg/m³
Consumer DI	NEL, acute	inhalation	systemic	155,2 mg/m³
Consumer DI	NEL, long-term	inhalation	local	14,7 mg/m³
Consumer DI	NEL, acute	inhalation	local	155,2 mg/m³
Canada Di	NEL, long-term	oral	systemic	4,2 mg/kg bw/day



according to UK REACH Regulation

DEKAPREN 1513/4

Revision date: 09.04.2025 Product code: 1078 Page 8 of 17

Consumer DNEL, long-term	dermal	systemic	4,2 mg/kg bw/day
123-86-4 n-butyl acetate			
Worker DNEL, long-term	inhalation	systemic	48 mg/m³
Worker DNEL, acute	inhalation	systemic	600 mg/m³
Worker DNEL, long-term	inhalation	local	300 mg/m³
Worker DNEL, acute	inhalation	local	600 mg/m³
Consumer DNEL, long-term	inhalation	systemic	12 mg/m³
Consumer DNEL, acute	inhalation	systemic	300 mg/m³
Consumer DNEL, long-term	inhalation	local	35,7 mg/m³
Consumer DNEL, acute	inhalation	local	300 mg/m³

PNEC values

CAS No	Substance			
Environmental	compartment	Value		
67-64-1	acetone; propan-2-one; propanone			
Freshwater	10,6 mg/l			
Marine water	Marine water			
Freshwater se	diment	30,4 mg/kg		
Marine sedime	ent	3,04 mg/kg		
Micro-organisr	ns in sewage treatment plants (STP)	100 mg/l		
Soil		29,5 mg/kg		
141-78-6	ethyl acetate	•		
Freshwater		0,24 mg/l		
Marine water		0,024 mg/l		
Freshwater se	diment	1,15 mg/kg		
Marine sedime	ent	0,115 mg/kg		
Secondary poi	Secondary poisoning			
Micro-organisr	ns in sewage treatment plants (STP)	650 mg/l		
Soil		0,148 mg/kg		
108-10-1	4-methylpentan-2-one, isobutyl methyl ketone			
Freshwater		0,6 mg/l		
Marine water		0,06 mg/l		
Freshwater se	diment	8,27 mg/kg		
Marine sedime	ent	0,83 mg/kg		
Micro-organisr	ns in sewage treatment plants (STP)	27,5 mg/l		
Soil		1,3 mg/kg		
123-86-4	n-butyl acetate			
Freshwater		0,18 mg/l		
Marine water		0,018 mg/l		
Freshwater se	Freshwater sediment			
Marine sedime	Marine sediment			
Micro-organisr	ns in sewage treatment plants (STP)	35,6 mg/l		
Soil				

8.2. Exposure controls



according to UK REACH Regulation

DEKAPREN 1513/4

Revision date: 09.04.2025 Product code: 1078 Page 9 of 17





Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (DIN EN 166)

Hand protection

Recommended glove articles:

FKM (fluoro rubber), Breakthrough time:: 480 min. NBR (Nitrile rubber), Breakthrough time:: 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141)., Filter material/medium: AX

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: light yellow transparent

Odour: characteristic
Odour threshold: not determined

Test method

Melting point/freezing point:

Boiling point or initial boiling point and

56 °C

boiling range:

Flammability:
Lower explosion limits:

Upper explosion limits:

13 vol. %

Flash point:

Auto-ignition temperature:

Decomposition temperature:

Highly flammable
2,1 vol. %

13 vol. %

-17 °C

Auto-ignition temperature:

373 °C

not determined

pH-Value: The study does not need to be conducted because the substance is

known to be insoluble in water.

Viscosity / kinematic: > 20,5 mm²/s

(at 40 °C)

Water solubility: Immiscible

Solubility in other solvents not determined

Partition coefficient n-octanol/water: not determined



according to UK REACH Regulation

DEKAPREN 1513/4

Revision date: 09.04.2025 Product code: 1078 Page 10 of 17

Vapour pressure: 240 hPa

(at 20 °C)

Vapour pressure: 828 hPa

(at 50 °C)

Density (at 20 °C): 0,91 g/cm³ DIN 51757

Relative vapour density: not determined Particle characteristics: not applicable

9.2. Other information

Information with regard to physical hazard classes

Explosive properties not determined

Sustained combustibility:

No data available

Self-ignition temperature

Solid: not self-igniting
Gas: not self-igniting

Oxidizing properties not determined

Other safety characteristics

Solvent content: 68,7 %
Solid content: 31,3%
Softening point: not determined
Viscosity / dynamic: 4767 mPa·s

(at 20 °C)

Further InformationNo information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

Further information

No further relevant information available.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix tested

Dose Species Source

LC50, inhalation (vapour) (4 h) 246 - 491 mg/l



according to UK REACH Regulation

DEKAPREN 1513/4

Revision date: 09.04.2025 Product code: 1078 Page 11 of 17

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation dust/mist) > 12,5 mg/l

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
67-64-1	acetone; propan-2-one; propanone							
	oral	LD50 mg/kg	5800	Rat	RTECS			
	dermal	LD50 15800 mg	7426- g/kg	Rabbit	IUCLID			
	inhalation (4 h) vapour	LC50	76 mg/l	Rat				
141-78-6	ethyl acetate							
	oral	LD50 mg/kg	5620	Rat				
	dermal	LD50 mg/kg	>20000	Rabbit				
	inhalation (4 h) vapour	LC50	50 mg/l	Rat				
79-20-9	methyl acetate							
	oral	LD50 mg/kg	>5000	Rat				
	dermal	LD50 mg/kg	>2000	Rabbit				
	inhalation (4 h) vapour	LC50	>49 mg/l	Rat				
108-10-1	4-methylpentan-2-one, is	sobutyl met	hyl ketone					
	oral	LD50 mg/kg	2080	Rat				
	inhalation vapour	ATE 11	mg/l					
123-86-4	n-butyl acetate							
	oral	LD50 mg/kg	10760	Rat				
	dermal	LD50 mg/kg	> 14112	Rabbit				
	inhalation vapour	LC50	> 21 mg/l	Rat				
	inhalation (4 h) dust/mist	LC50	>21 mg/l	Rat				

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (4-methylpentan-2-one, isobutyl methyl ketone)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (acetone; propan-2-one; propanone)

STOT-repeated exposure

Based on available data, the classification criteria are not met.



according to UK REACH Regulation

DEKAPREN 1513/4

Revision date: 09.04.2025 Product code: 1078 Page 12 of 17

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No information available.

Specific effects in experiment on an animal

No information available.

Additional information on tests

No information available.

Practical experience

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone						
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss		
	Acute crustacea toxicity	EC50 mg/l	8800	48 h	Daphnia Magna		
	Algae toxicity	NOEC mg/l	4740	2 d	Selenastrum capricornutum		
141-78-6	ethyl acetate						
	Acute fish toxicity	LC50	230 mg/l	96 h	Pimephales promelas (fathead minnow)		
	Acute algae toxicity	ErC50 mg/l	3300		Desmodesmus subspicatus	48 h	
	Acute crustacea toxicity	EC50	717 mg/l	48 h	Daphnia magna (Big water flea)		
	Acute bacteria toxicity	EC50 mg/l ()	2900		Pseudomonas putida	16 h	
108-10-1	4-methylpentan-2-one, iso	obutyl methy	yl ketone				
	Acute fish toxicity	LC50	179 mg/l	96 h	Danio rerio (zebrafish)		
	Acute crustacea toxicity	EC50 mg/l	>200	48 h	Daphnia magna	IUCLID	
	Crustacea toxicity	NOEC mg/l	30-35	21 d	Daphnia magna		
123-86-4	n-butyl acetate						
	Acute fish toxicity	LC50	18 mg/l	96 h	Pimephales promelas (fathead minnow)		
	Acute algae toxicity	ErC50	397 mg/l	72 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50	44 mg/l	48 h	Daphnia magna (Big water flea)		



according to UK REACH Regulation

DEKAPREN 1513/4

Revision date: 09.04.2025 Product code: 1078 Page 13 of 17

12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name						
	Method	Value	d	Source			
	Evaluation	-	-				
67-64-1	acetone; propan-2-one; propanone						
	OECD 301 B	91%	28				
	Readily biodegradable (according to OECD criteria).						
141-78-6	ethyl acetate						
	OECD 301D/ EEC 92/69/V, C.4-E	100 %	28				
	Readily biodegradable (according to OECD criteria).						
108-10-1	4-methylpentan-2-one, isobutyl methyl ketone						
	OECD 301 F	83 %	28				
	Readily biodegradable (according to OECD criteria).						
123-86-4	n-butyl acetate						
	OECD 301D/ EEC 92/69/V, C.4-E	83%	28				
	Readily biodegradable (according to OECD criteria).		·				

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24
141-78-6	ethyl acetate	0,73
79-20-9	methyl acetate	0,18
108-10-1	4-methylpentan-2-one, isobutyl methyl ketone	1,38
123-86-4	n-butyl acetate	2,3

BCF

CAS No	Chemical name	BCF	Species	Source
67-64-1	acetone; propan-2-one; propanone	<10		

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

Do not mix with other wastes.



according to UK REACH Regulation

DEKAPREN 1513/4

Revision date: 09.04.2025 Product code: 1078 Page 14 of 17

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

 ${\tt COATINGS~(PAINTS,~VARNISHES~AND~VITREOUS~ENAMELS),~ADHESIVES,~SEALANTS~AND~PRINTING~INKS;~wastes~from~MFSU~of~adhesives~and~sealants~(including~waterproofing~products);}$

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

Contaminated packaging

Dispose according to legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1133 **14.2. UN proper shipping name:** ADHESIVES

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 640D
Limited quantity: 5 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Other applicable information (land transport)

Protect against:Freeze

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1133 **14.2. UN proper shipping name:** Adhesives

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 640D
Limited quantity: 5 L
Excepted quantity: E2

Other applicable information (inland waterways transport)

Protect against:Freeze

Marine transport (IMDG)

14.1. UN number or ID number: UN 1133 **14.2. UN proper shipping name:** ADHESIVES

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label:

3



according to UK REACH Regulation

DEKAPREN 1513/4

Revision date: 09.04.2025 Product code: 1078 Page 15 of 17



Marine pollutant:

Special Provisions:

Limited quantity:

Excepted quantity:

E2

EmS:

F-E, S-D

Other applicable information (marine transport)

Protect against:Freeze

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1133 **14.2. UN proper shipping name:** ADHESIVES

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A3

1 L

Y341

Excepted quantity:

E2

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

Other applicable information (air transport)

Protect against:Freeze

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable liquids

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in 68,74 % paints and varnishes: 625,5 g/l

Information according to Directive P5c FLAMMABLE LIQUIDS

2012/18/EU (SEVESO III):

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant

disappearances and thefts should be reported to the relevant national contact point.

Additional information

Observe in addition any national regulations!



according to UK REACH Regulation

DEKAPREN 1513/4

Revision date: 09.04.2025 Product code: 1078 Page 16 of 17

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the

Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,15,16.

Abbreviations and acronyms

Flam. Liq: Flammable liquids Acute Tox: Acute toxicity Eye Irrit: Eye irritation Carc: Carcinogenicity

STOT SE: Specific target organ toxicity - single exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure	
Flam. Liq. 2; H225	On basis of test data	
Carc. 2; H351	Calculation method	
Eye Irrit. 2; H319	Calculation method	
STOT SE 3; H336	Calculation method	

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.H351 Suspected of causing cancer.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be

Print date: 09.04.2025



Safety Data Sheet

according to UK REACH Regulation

DEKAPREN 1513/4

Revision date: 09.04.2025 Product code: 1078 Page 17 of 17

transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)