

Safety Data Sheet

according to UK REACH Regulation

PLASTIGUM 77

Revision date: 16.04.2025

Product code: 1082

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

PLASTIGUM 77

UFI: 0WY2-T0N4-500T-JS3T

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Sizing agent

Uses advised against

No further relevant information available.

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: DINOL GmbH
Street: Pyrmonter Strasse 76
Place: D-32676 Luegde
Telephone: + 49 (0) 5281 982980
E-mail: msds@dinol.com
Contact person: Labor
Responsible Department: msds@dinol.com

Telefax: + 49 (0) 5281 9829860

Supplier

Company name: Leading Solvent Supplies Limited
Street: Marston Business Park, Rudgate
Place: GB Tockwith, York YO26 7QF
E-mail: enquiries@leading-solvents.co.uk
Internet: www.leading-solvents.co.uk

1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Flam. Liq. 2; H225
Repr. 2; H361d
Skin Irrit. 2; H315
Eye Irrit. 2; H319
STOT SE 3; H336
STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**

acetone; propan-2-one; propanone
toluene

Signal word: Danger

Safety Data Sheet

according to UK REACH Regulation

PLASTIGUM 77

Revision date: 16.04.2025

Product code: 1082

Page 2 of 14

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take action to prevent static discharges.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Special labelling of certain mixtures

Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H361d

Precautionary statements

P280-P405

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to UK REACH Regulation

PLASTIGUM 77

Revision date: 16.04.2025

Product code: 1082

Page 3 of 14

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
67-64-1	acetone; propan-2-one; propanone			55 - < 60 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
108-88-3	toluene			20 - < 25 %
	203-625-9	601-021-00-3	01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H336 H373 H304 H412			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
67-64-1	200-662-2	acetone; propan-2-one; propanone	55 - < 60 %
		inhalation: LC50 = 76 mg/l (vapours); dermal: LD50 = 7426-15800 mg/kg; oral: LD50 = 5800 mg/kg	
108-88-3	203-625-9	toluene	20 - < 25 %
		inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg	

Further Information

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Do NOT induce vomiting.

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

Safety Data Sheet

according to UK REACH Regulation

PLASTIGUM 77

Revision date: 16.04.2025

Product code: 1082

Page 4 of 14

5.1. Extinguishing media**Suitable extinguishing media**alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder,**Unsuitable extinguishing media**

High power water jet.

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Use appropriate respiratory protection.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Safety Data Sheet

according to UK REACH Regulation

PLASTIGUM 77

Revision date: 16.04.2025

Product code: 1082

Page 5 of 14

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in a cool dry place.

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed.
Keep in a cool, well-ventilated place.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL

Safety Data Sheet

according to UK REACH Regulation

PLASTIGUM 77

Revision date: 16.04.2025

Product code: 1082

Page 6 of 14

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
67-64-1	acetone; propan-2-one; propanone			
Worker DNEL, long-term		inhalation	systemic	1210 mg/m³
Worker DNEL, acute		inhalation	local	2420 mg/m³
Worker DNEL, long-term		dermal	systemic	186 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	200 mg/m³
Consumer DNEL, long-term		dermal	systemic	62 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	62 mg/kg bw/day
,				
108-88-3	toluene			
Worker DNEL, long-term		inhalation	systemic	192 mg/m³
Worker DNEL, long-term		inhalation	local	192 mg/m³
Worker DNEL, acute		inhalation	systemic	384 mg/m³
Worker DNEL, acute		inhalation	local	384 mg/m³
Worker DNEL, long-term		dermal	systemic	384 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	56,5 mg/m³
Consumer DNEL, long-term		inhalation	local	56,5 mg/m³
Consumer DNEL, acute		inhalation	systemic	226 mg/m³
Consumer DNEL, acute		inhalation	local	226 mg/m³
Consumer DNEL, long-term		dermal	systemic	226 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	8,13 mg/kg bw/day

PNEC values

CAS No	Substance	
Environmental compartment	Value	
67-64-1	acetone; propan-2-one; propanone	
Freshwater	10,6 mg/l	
Marine water	1,06 mg/l	
Freshwater sediment	30,4 mg/kg	
Marine sediment	3,04 mg/kg	
Micro-organisms in sewage treatment plants (STP)	100 mg/l	
Soil	29,5 mg/kg	
108-88-3	toluene	
Freshwater	0,68 mg/l	
Freshwater sediment	16,39 mg/kg	
Micro-organisms in sewage treatment plants (STP)	13,61 mg/l	
Soil	13,61 mg/l	

8.2. Exposure controls

Safety Data Sheet

according to UK REACH Regulation

PLASTIGUM 77

Revision date: 16.04.2025

Product code: 1082

Page 7 of 14



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (DIN EN 166)

Hand protection

Recommended glove articles :

FKM (fluoro rubber), Breakthrough time:: 480 min.

NBR (Nitrile rubber), Breakthrough time:: 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141)., Filter material/medium: AX

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	translucent
Odour:	characteristic
Odour threshold:	not determined

Test method

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	56 °C
Flammability:	Highly flammable
Lower explosion limits:	1,2 vol. %
Upper explosion limits:	13 vol. %
Flash point:	-17 °C
Auto-ignition temperature:	465 °C
Decomposition temperature:	not determined
pH-Value:	The study does not need to be conducted because the substance is known to be insoluble in water.
Viscosity / kinematic: (at 40 °C)	> 20,5 mm²/s
Water solubility:	Immiscible
Solubility in other solvents not determined	
Partition coefficient n-octanol/water:	not determined

Safety Data Sheet

according to UK REACH Regulation

PLASTIGUM 77

Revision date: 16.04.2025

Product code: 1082

Page 8 of 14

Vapour pressure: (at 20 °C)	240 hPa
Vapour pressure: (at 50 °C)	828 hPa
Density (at 20 °C):	0,86 g/cm ³ DIN 51757
Relative vapour density:	not determined
Particle characteristics:	not applicable

9.2. Other information

Information with regard to physical hazard classes

Explosive properties	
not determined	
Sustained combustibility:	No data available
Self-ignition temperature	
Solid:	not self-igniting
Gas:	not self-igniting
Oxidizing properties	
not determined	

Other safety characteristics

Solvent content:	79,5 %
Solid content:	20,6
Softening point:	not determined
Viscosity / dynamic: (at 20 °C)	2750 mPa·s

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

Further information

No further relevant information available.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to UK REACH Regulation

PLASTIGUM 77

Revision date: 16.04.2025

Product code: 1082

Page 9 of 14

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50 5800 mg/kg	Rat	RTECS	
	dermal	LD50 7426-15800 mg/kg	Rabbit	IUCLID	
	inhalation (4 h) vapour	LC50 76 mg/l	Rat		
108-88-3	toluene				
	oral	LD50 5580 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg			
	inhalation (4 h) vapour	LC50 28,1 mg/l	Rat		

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (acetone; propan-2-one; propanone; toluene)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (toluene)

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No information available.

Specific effects in experiment on an animal

No information available.

Additional information on tests

No information available.

Practical experience

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to UK REACH Regulation

PLASTIGUM 77

Revision date: 16.04.2025

Product code: 1082

Page 10 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50 mg/l	8800	48 h	Daphnia Magna	
	Algae toxicity	NOEC mg/l	4740	2 d	Selenastrum capricornutum	
108-88-3	toluene					
	Acute algae toxicity	ErC50 mg/l	12,5	72 h	alga	
	Acute crustacea toxicity	EC50	3,8 mg/l	48 h	Daphnia magna (Big water flea)	

12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
67-64-1	acetone; propan-2-one; propanone			
	OECD 301 B	91%	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24
108-88-3	toluene	2,73

BCF

CAS No	Chemical name	BCF	Species	Source
67-64-1	acetone; propan-2-one; propanone	<10		

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

Safety Data Sheet

according to UK REACH Regulation

PLASTIGUM 77

Revision date: 16.04.2025

Product code: 1082

Page 11 of 14

Do not mix with other wastes.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Dispose according to legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1133
14.2. UN proper shipping name: ADHESIVES
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 640D
Limited quantity: 5 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Other applicable information (land transport)

Protect against: Freeze

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 640D
Limited quantity: 5 L
Excepted quantity: E2

Other applicable information (inland waterways transport)

Protect against: Freeze

Marine transport (IMDG)

14.1. UN number or ID number: UN 1133
14.2. UN proper shipping name: ADHESIVES
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3

Safety Data Sheet

according to UK REACH Regulation

PLASTIGUM 77

Revision date: 16.04.2025

Product code: 1082

Page 12 of 14



Marine pollutant: no
Special Provisions: -
Limited quantity: 5 L
Excepted quantity: E2
EmS: F-E, S-D

Other applicable information (marine transport)

Protect against: Freeze

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1133
14.2. UN proper shipping name: ADHESIVES
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

Other applicable information (air transport)

Protect against: Freeze

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable liquids

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

Transport classification ADR/IMDG is based on packaging >30ltr(IMDG), <450ltr(ADR).
For other packaging until different classification can apply.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):
Entry 3, Entry 40, Entry 48, Entry 75

Directive 2004/42/EC on VOC in
paints and varnishes: 79,48 %
683,6 g/l
Information according to Directive
2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS
Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

Safety Data Sheet

according to UK REACH Regulation

PLASTIGUM 77

Revision date: 16.04.2025

Product code: 1082

Page 13 of 14

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,9,15,16.

Abbreviations and acronyms

Flam. Liq: Flammable liquids

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Repr. 2; H361d	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method

Relevant H and EUH statements (number and full text)

H225

Highly flammable liquid and vapour.

Safety Data Sheet

according to UK REACH Regulation

PLASTIGUM 77

Revision date: 16.04.2025

Product code: 1082

Page 14 of 14

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)