



DEKARUST REMOVER

Power rust remover

DEKARUST REMOVER is a premium rust remover that is ideal for loosening rusted screws/nuts and dissolving rust on all corroded surfaces. Fast-acting, high-performance rust remover. Immediately penetrates difficult-to-reach places. Loosens jammed mechanical systems, removes rust and oil/grease.

DEKARUST REMOVER			
Art. No.	Size	Container	Colour
61420 34	250 ml	Spray can	Transparent

Your advantages:

- **Unique active formula**
- **Dissolves rust and encrusted grime**
- **Immediately penetrates difficult-to-reach places**
- **No silicones, no mineral oils**
- **No paint wetting impairment substances (PWIS)**
- **Highly concentrated, universal usage**
- **Easy to apply with the perfectly adapted spraying straw**
- **Environmentally friendly**

DEKARUST REMOVER **Power rust remover**

Technical Details

Product description

DEKARUST REMOVER is a premium rust remover that is ideal for loosening rusted screws/nuts and dissolving rust on all corroded surfaces. Fast-acting, high-performance rust remover. Immediately penetrates difficult-to-reach places. Loosens jammed mechanical systems, removes rust and oil/grease. New formulation with three active ingredients allows for deep penetration. Rust is destroyed and removed from the surface. Depletes slowly and can work for several hours. Can be used to clean specific spots or for general cleaning.

Applications

- All types of corroded parts that need to be loosened or have corrosion removed.

Method of Use

No pre-treatment required. Apply DEKARUST REMOVER to the problematic area and give it time to work and penetrate into the parts. Maximum time to work: 24 h. Use a brush to clean the surfaces of the area where DEKARUST REMOVER was applied to allow the product to penetrate deeper into the corrosion. Reapply and repeat the process if necessary. For the properties of substrates that are not on the list and for more detailed information, please contact your DEKALIN customer service directly.

Storage

DEKARUST REMOVER can be stored in a sealed (unopened) container in a dry place at temperatures between +5°C and +30°C for 24 months.

Please note: Do not store DEKARUST REMOVER in the passenger cab of vehicles, as the container may explode at temperatures above 50°C.

Safety precautions

Please consult our current material safety data sheet for further information.

Transport classification

Please consult our current material safety data sheet for further information.

Technical Data

Colour (standard)	Transparent
Base	Aqueous special surfactant solution
Film type	Oily
Fragrance	Cinnamon
Specific density (20°C)	approx. 0.84 kg/l
Flash point	approx. -20°C
Container sizes	250 ml spray can

Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation
Aerosol 1; H222-H229

Consult the safety data sheet

or the container label for safety notes.