

**DEKAPHON 225 Metallic**

Revision: 07.01.2026

Product code: 20225

Page 1 of 12

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

DEKAPHON 225 Metallic

UFI: 8YCP-GTN8-K50X-Q5AM

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**

Korrosionsschutzmittel

**1.3. Details of the supplier of the safety data sheet**

**Manufacturer**

|                         |                      |                                |
|-------------------------|----------------------|--------------------------------|
| Company name:           | DINOL GmbH           |                                |
| Street:                 | Pyrmonter Strasse 76 |                                |
| Place:                  | D-32676 Luegde       |                                |
| Telephone:              | + 49 (0) 5281 982980 | Telefax: + 49 (0) 5281 9829860 |
| E-mail:                 | msds@dinol.com       |                                |
| Contact person:         | Labor                |                                |
| Internet:               | www.dinol.com        |                                |
| Responsible Department: | msds@dinol.com       |                                |

**Supplier**

|               |                                  |
|---------------|----------------------------------|
| Company name: | Leading Solvent Supplies Limited |
| Street:       | Marston Business Park, Rudgate   |
| Place:        | GB Tockwith, York YO26 7QF       |
| E-mail:       | enquiries@leading-solvents.co.uk |
| Internet:     | www.leading-solvents.co.uk       |

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

**1.4. Emergency telephone number:**

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Regulation (EC) No 1272/2008**

Flam. Liq. 3; H226  
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

**2.2. Label elements**

**Regulation (EC) No 1272/2008**

**Hazard components for labelling**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

**Signal word:** Warning

**Pictograms:**



**Hazard statements**

|        |   |
|--------|---|
| H226   | Flammable liquid and vapour.                          |
| H336   | May cause drowsiness or dizziness.                    |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

**DEKAPHON 225 Metallic**

Revision: 07.01.2026

Product code: 20225

Page 2 of 12

**Precautionary statements**

|                |  |
|----------------|--|
| P210           | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.         |
| P280           | Wear protective gloves and eye protection/face protection.   |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. |
| P403+P235      | Store in a well-ventilated place. Keep cool.   |
| P405           | Store locked up.   |

**Special labelling**

Restricted to professional users.

**Labelling of packages where the contents do not exceed 125 ml**
**Signal word:** Warning

**Pictograms:**

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients**
**3.2. Mixtures**
**Relevant ingredients**

| CAS No    | Chemical name   | Quantity         |
|-----------|---|------------------|
|           | EC No   | Index No         |
|           | REACH No  |                  |
|           | Classification (Regulation (EC) No 1272/2008)                       |                  |
|           | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | 45 - < 50 %      |
|           | 919-857-5   | 01-2119463258-33 |
|           | Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066         |                  |
| 7429-90-5 | aluminium powder (stabilised)                                       | 1 - < 5 %        |
|           | 231-072-3   | 01-2119529243-45 |
|           | Flam. Sol. 1; H228  |                  |
| 64-17-5   | ethanol; ethyl alcohol  | 1 - < 5 %        |
|           | 200-578-6   | 603-002-00-5     |
|           | 01-2119457610-43  |                  |
|           | Flam. Liq. 2; H225  |                  |

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

| CAS No  | EC No     | Chemical name  | Quantity    |
|---------|-----------|--|-------------|
|         |           | Specific Conc. Limits, M-factors and ATE   |             |
|         | 919-857-5 | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics                              | 45 - < 50 % |
|         |           | inhalation: LC50 = > 5000 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg |             |
| 64-17-5 | 200-578-6 | ethanol; ethyl alcohol   | 1 - < 5 %   |
|         |           | inhalation: LC50 = 20000 mg/l (vapours); oral: LD50 = 7060 mg/kg                                 |             |

**Further Information**

Hydrocarbons meet the requirements for not being classified as carcinogenic (&lt;0,1% benzene alt&lt;3% (w/w) DMSO extract (IP 346)).

**DEKAPHON 225 Metallic**

Revision: 07.01.2026

Product code: 20225

Page 3 of 12

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice.  
 Never give anything by mouth to an unconscious person or a person with cramps.  
 If unconscious but breathing normally, place in recovery position and seek medical advice.

**After inhalation**

Remove casualty to fresh air and keep warm and at rest.

**After contact with skin**

Change contaminated clothing.  
 After contact with skin, wash immediately with plenty of water and soap.

**After contact with eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
 Continue rinsing. Seek medical advice immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious).  
 Do NOT induce vomiting.  
 Call a physician immediately.  
 Put victim at rest, cover with a blanket and keep warm.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>); Extinguishing powder; Sand; alcohol resistant foam

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

No information available.

**5.3. Advice for firefighters**

Use appropriate respiratory protection.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.  
 Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**General advice**

Provide adequate ventilation.  
 Wear personal protection equipment.  
 Avoid contact with skin, eyes and clothes.  
 Avoid breathing dust/fume/gas/mist/vapours/spray.

**For emergency responders**

For further specification, refer to section 8 of the SDS.

**DEKAPHON 225 Metallic**

Revision: 07.01.2026

Product code: 20225

Page 4 of 12

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment.  
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up**

**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).  
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).  
Treat the recovered material as prescribed in the section on waste disposal.

**For cleaning up**

Provide adequate ventilation.  
Clear contaminated areas thoroughly.  
Do not rinse down with water.

**Other information**

No information available.

**6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used.  
If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.  
Take precautionary measures against static discharges.

**Advice on general occupational hygiene**

The usual precautionary measures are to be adhered to when handling chemicals.  
Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.  
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

No special measures are necessary.

**Hints on joint storage**

Not required.

**Further information on storage conditions**

Keep container tightly closed.

**7.3. Specific end use(s)**

No information available.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**DEKAPHON 225 Metallic**

Revision: 07.01.2026

Product code: 20225

Page 5 of 12

**Exposure limits (EH40)**

| CAS No    | Substance                        | ppm  | mg/m <sup>3</sup> | fibres/ml | Category  | Origin |
|-----------|----------------------------------|------|-------------------|-----------|-----------|--------|
| 7429-90-5 | Aluminium metal, inhalable dust  | -    | 10                |           | TWA (8 h) | WEL    |
| 7429-90-5 | Aluminium metal, respirable dust | -    | 4                 |           | TWA (8 h) | WEL    |
| 64-17-5   | Ethanol                          | 1000 | 1920              |           | TWA (8 h) | WEL    |

**DNEL/DMEL values**

| CAS No  | Substance | Exposure route | Effect   | Value                 |
|---|-----------|----------------|----------|-----------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics |           |                |          |                       |
| Consumer DNEL, long-term  |           | oral           | systemic | 125 mg/kg bw/day      |
| Worker DNEL, long-term  |           | dermal         | systemic | 208 mg/kg bw/day      |
| Consumer DNEL, long-term  |           | dermal         | systemic | 125 mg/kg bw/day      |
| Worker DNEL, long-term  |           | inhalation     | systemic | 871 mg/m <sup>3</sup> |
| Consumer DNEL, long-term  |           | inhalation     | systemic | 185 mg/m <sup>3</sup> |

**8.2. Exposure controls**



**Appropriate engineering controls**

Provide adequate ventilation.  
 If handled uncovered, arrangements with local exhaust ventilation should be used if possible.  
 If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Eye glasses with side protection (EN 166)

**Hand protection**

Tested protective gloves must be worn (EN ISO 374):  
 FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.  
 NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.  
 Thickness of the glove material : > 0,12 mm  
 For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.  
 Protective gloves have to be replaced at the first sign of deterioration.  
 Protect skin by using skin protective cream.

**Skin protection**

Wear anti-static footwear and clothing

**Respiratory protection**

Work in well-ventilated zones or use proper respiratory protection.  
 gas filtering equipment (EN 141)., Filter material/medium: A

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state: viscous  
 Colour: brown

**DEKAPHON 225 Metallic**

Revision: 07.01.2026

Product code: 20225

Page 6 of 12

Odour: characteristic  
 Odour threshold: not determined

**Test method**

Melting point/freezing point: not determined  
 Boiling point or initial boiling point and boiling range: 154 - 193 °C  
 Flammability: not applicable  
 Lower explosion limits: 0,7 vol. %  
 Upper explosion limits: 6 vol. %  
 Flash point: 36 °C  
 Auto-ignition temperature: > 200 °C  
 Decomposition temperature: not determined

pH-Value: The study does not need to be conducted because the substance is known to be insoluble in water.  
 > 20,5 mm<sup>2</sup>/s

Viscosity / kinematic: (at 40 °C) > 20,5 mm<sup>2</sup>/s

Water solubility: practically insoluble

Solubility in other solvents: not determined

Partition coefficient n-octanol/water: not determined

Vapour pressure: (at 20 °C) 3 hPa

Vapour pressure: (at 50 °C) 13 hPa

Density (at 20 °C): 1,11 - 1,14 g/cm<sup>3</sup> DIN 51757

Relative vapour density: not determined

Particle characteristics: not applicable

**9.2. Other information**

**Information with regard to physical hazard classes**

Explosive properties

The product is: not explosive.. In use, may form flammable/explosive vapour-air mixture.

Sustained combustibility: No data available

Oxidizing properties

not determined

**Other safety characteristics**

Evaporation rate: not determined

Solvent content: 31,3 %

Solid content: 66 - 70

Softening point: not determined

Viscosity / dynamic: (at 20 °C) 2000 - 4000 mPa·s

**Further Information**

No information available.

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No further relevant information available.

**10.2. Chemical stability**

No known hazardous decomposition products.

**10.3. Possibility of hazardous reactions**

**DEKAPHON 225 Metallic**

Revision: 07.01.2026

Product code: 20225

Page 7 of 12

No known hazardous reactions.

**10.4. Conditions to avoid**

No further relevant information available.

**10.5. Incompatible materials**

No further relevant information available.

**10.6. Hazardous decomposition products**

Carbon monoxide

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes**

**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

| CAS No  | Chemical name   |                   |         |        |        |
|---------|---|-------------------|---------|--------|--------|
|         | Exposure route  | Dose              | Species | Source | Method |
|         | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics |                   |         |        |        |
|         | oral  | LD50 > 5000 mg/kg | Rat     |        |        |
|         | dermal  | LD50 > 5000 mg/kg | Rabbit  |        |        |
|         | inhalation (4 h) vapour   | LC50 > 5000 mg/l  | Rat     |        |        |
| 64-17-5 | ethanol; ethyl alcohol  |                   |         |        |        |
|         | oral  | LD50 7060 mg/kg   | Rat     |        |        |
|         | inhalation (4 h) vapour   | LC50 20000 mg/l   | Rat     |        |        |

**Irritation and corrosivity**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

No information available.

**DEKAPHON 225 Metallic**

Revision: 07.01.2026

Product code: 20225

Page 8 of 12

**Specific effects in experiment on an animal**

No information available.

**Additional information on tests**

No information available.

**Practical experience**

No information available.

**11.2. Information on other hazards**

**Endocrine disrupting properties**

Endocrine disrupting potential No information available.

**Further information**

There are no data available on the preparation/mixture itself.

**SECTION 12: Ecological information**

**12.1. Toxicity**

Based on available data, the classification criteria are not met.

| CAS No  | Chemical name            |               |           |         |               |        |
|---------|--------------------------|---------------|-----------|---------|---------------|--------|
|         | Aquatic toxicity         | Dose          | [h]   [d] | Species | Source        | Method |
| 64-17-5 | ethanol; ethyl alcohol   |               |           |         |               |        |
|         | Acute fish toxicity      | LC50<br>mg/l  | 13000     | 96 h    | fish          |        |
|         | Acute algae toxicity     | ErC50<br>mg/l | 5000      | 72 h    | alga          |        |
|         | Acute crustacea toxicity | EC50<br>mg/l  | 9300      | 48 h    | Daphnia magna | IUCLID |

**12.2. Persistence and degradability**

No further relevant information available.

| CAS No | Chemical name   |       |   |        |
|--------|---|-------|---|--------|
|        | Method  | Value | d | Source |
|        | Evaluation  |       |   |        |
|        | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics |       |   |        |
|        |   | 80%   |   |        |
|        | Readily biodegradable (according to OECD criteria).                 |       |   |        |

**12.3. Bioaccumulative potential**

No further relevant information available.

**Partition coefficient n-octanol/water**

| CAS No  | Chemical name          | Log Pow |
|---------|------------------------|---------|
| 64-17-5 | ethanol; ethyl alcohol | -0,31   |

**12.4. Mobility in soil**

No further relevant information available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No further relevant information available.

**DEKAPHON 225 Metallic**

Revision: 07.01.2026

Product code: 20225

Page 9 of 12

**Further information**

There are no data available on the mixture itself.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations**

Dispose of waste according to applicable legislation.  
Do not mix with other wastes.

**List of Wastes Code - residues/unused products**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**List of Wastes Code - contaminated packaging**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**Contaminated packaging**

Dispose of waste according to applicable legislation.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** COATING SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 5 L  
 Excepted quantity: E1  
 Transport category: 3  
 Hazard No: 30  
 Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** Coating solution  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 5 L  
 Excepted quantity: E1

**Marine transport (IMDG)**

**DEKAPHON 225 Metallic**

Revision: 07.01.2026

Product code: 20225

Page 10 of 12

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** COATING SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Marine pollutant: no  
Limited quantity: 5 L  
Excepted quantity: E1  
EmS: F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** COATING SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Special Provisions: A3  
Limited quantity Passenger: 10 L  
Passenger LQ: Y344  
Excepted quantity: E1  
IATA-packing instructions - Passenger: 355  
IATA-max. quantity - Passenger: 60 L  
IATA-packing instructions - Cargo: 366  
IATA-max. quantity - Cargo: 220 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Flammable liquids

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: 31,27 %  
350,2 g/l  
Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

**Additional information**

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

**DEKAPHON 225 Metallic**

Revision: 07.01.2026

Product code: 20225

Page 11 of 12

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

**Additional information**

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

86161

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 2,7,8,11,16.

**Abbreviations and acronyms**

- Flam. Liq. 2: Flammable liquids, hazard category 2
- Flam. Liq. 3: Flammable liquids, hazard category 3
- Flam. Sol. 1: Flammable solids, hazard category 1
- Asp. Tox. 1: Aspiration hazard, hazard category 1
- STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service
- LC50: Lethal concentration, 50%
- LD50: Lethal dose, 50%

**Classification for mixtures and used evaluation method**

| Classification     | Classification procedure |
|--------------------|--------------------------|
| Flam. Liq. 3; H226 | On basis of test data    |
| STOT SE 3; H336    | Calculation method       |

**Relevant H and EUH statements (number and full text)**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H304 May be fatal if swallowed and enters airways.
- H336 May cause drowsiness or dizziness.
- EUH066 Repeated exposure may cause skin dryness or cracking.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

**DEKAPHON 225 Metallic**

Revision: 07.01.2026

Product code: 20225

Page 12 of 12

This safety data sheet contains only safety-related information and does not replace product information or product specifications.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*